



PRODUCT OVERVIEW

The Envoltage 2400W portable power station is the portable power station with the largest energy storage capacity. Whether it is a high-power device at home or a high-power device for outdoor work, it can continue to supply power and can be used as a backup power supply for power failure at home and field camping. And it supports solar charging to store power for your devices anytime, anywhere.

FEATURES

- 14 output ports compatible with multiple devices
- 3 flexible ways to recharge
- Over-current, over-voltage, and over-temperature protection
- Environmentally friendly / No gas / Quieter / Cost-effective

ADVANTAGES

- 2232Wh Capacity | 2400W AC Pure Sine Wave Inverter (5000W Surge)
- 5 x 2400W AC Ports
- LiFePO4 Battery with 3,500+ Life Cycles to 80%
- 14 Outputs For Multiple Devices
- 5 Ways to Recharge (AC/Solar/Car/AC+Solar/Dual AC)
- Smart HD LCD display
- LED Soft Lighting & SOS Signal
- 1000W Max. Input charging speed
- Anderson Recharging Input
- Power for 95% of appliances

DISCHARGE CAPABILITIES

- Phone/11Wh – 155 charges
- Laptop/60Wh – 30 charges
- Electric Grill/1500W – 1.3 hours
- Speaker/35W – 51 hours
- Projector/100W – 17 hours
- Blender/300W – 6 hours
- Air Conditioner/8000BTU – 4~8 hours
- Coffee Maker/500W – 3.6 hours
- Microwave/800W – 2.7 hours
- Refrigerator/150W – 17~30 hours

Product Description

PART#	DESCRIPTION	CAPACITY	INPUT	AC OUTPUT
EV-UPP-2400	Portable Power Station	2232Wh	2 ports, 400W Max	5 Outlets, 2400W (Surge 4000W)

Specifications

MODEL#		EV-UPP-2400
CAPACITY		
Capacity	2232Wh	
BATTERY		
Battery Chemistry	LFP (LiFePO4)	
Cycle Life	3500+ cycles to 80% capacity	
BMS	Yes	
OUTPUT		
AC Output	5 outlets, 2400W (surge 4000W)	
DC Output	2 ports, 12V, 10A 120W Max	
USB-A	4 ports, QC 3.0. 18W Max	
USB-C	2 ports, 5/9/12/15/20V, 3A 60W Max	
Car Output	12V, 10A 120W Max	
INPUT		
AC Input	2 ports, 400W Max	
Solar Input	2 ports, 1000W Max, 12-45V	
Input Power	2*24V/200W Max	
GENERAL		
Net Weight	45.6 lbs	
Dimensions	16.5*10.6*12.3 in	
Operating Temperature	0°C~40°C/30°F~104°F	
Certification	UN38.3.MSDs	
Warranty	3 years	

Product Images



Product Features

